



Composition

- Reels-holder for tubular film
- Hot printing unit
- Tubes unwinding, cutting and positioning
- High frequency welding press pneumatically operated
- High frequency generator incorporated in the structure of the press
- Index device by a mobile clamp operating by a "Brushless" motor
- Automatic removal scrap unit
- Liquid circulation refrigerating unit
- Control panel with PLC (remote service on request)
- Push-button panel with touch screen

Technical characteristics

Reel maximum diameter:	400 mm
Reel maximum width:	450 mm
Press maximum closing force:	1600 kg
Press upper plate dimension:	450x600 mm
Press down plate dimension:	550x700 mm
Indexing unit forward (minimum - maximum):	150 ÷ 520 mm
Output power of the generator:	15 kW
Working frequency:	27.12 MHz ± 0.6%
Feeding voltage:	400 V - 3Ph+G - 50 Hz (other voltages on request)
Compressed air pressure:	0.6 Mpa
Item product:	EVA medical bags 1000 - 2000 - 3000 ml with 3 tubes for enteral and parenteral alimentation
Foreseen productivity:	800 pieces/hour (2000 ml bags)



Steinbachstraße 133
A 3001 Mauerbach
Austria
T+43 (0) | 577 24 18
F+43 (0) | 577 24 18 15
office@cm-tech.at
www.cm-tech.at